

CORRECTED VERSION

(19) World Intellectual Property
Organization
International Bureau



14 DEC 2004



(43) International Publication Date
14 August 2003 (14.08.2003)


PCT

(10) International Publication Number
WO 2003/067156 A3

- (51) International Patent Classification⁷: F25D 17/06, 23/00
- (21) International Application Number: PCT/US2003/003729
- (22) International Filing Date: 6 February 2003 (06.02.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 60/354,682 6 February 2002 (06.02.2002) US
- (71) Applicant and
(72) Inventor: MORATALLA, Jose [US/US]; 738 Heathrow Lane, Palm Harbor, FL 34683 (US).
- (74) Agent: EHRLICH, Henry, L.; WINSTEAD SECHREST & MINICK P.C., 910 Travis Street, 2400 Bank One Center, Houston, TX 77002 (US).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Declaration under Rule 4.17:
— of inventorship (Rule 4.17(iv)) for US only
- Published:
— with international search report

[Continued on next page]

(54) Title: DESICCANT DEHUMIDIFICATION SYSTEM



(57) Abstract: A desiccant dehumidification system (DDS) uses an air heater that incorporates air feedback from the exhaust (115) and/or the return air fans (206). The air and gas are mixed in a mixing valve (110). The mixing valve (110) may be a single step, a two step or a continuous modulation valve. An outdoor cooking grill style burner (12) allows a small unit to be made with tight air heating system. One system cools the return air making it cool and humid. A portion of this air is then dried by a DDS which makes output air that is hot and dry. The remaining return air is then dried by DDS output air to deliver processed air in a controlled comfort range. A second system mixes return air with fresh air to make mixed return air which is dried in a DDS. The dried return air is then cooled to a desired comfort range without condensation.

WO 2003/067156 A3

WO 2003/067156 A3



(88) Date of publication of the international search report:
19 February 2004

(15) Information about Correction:
see PCT Gazette No. 14/2004 of 1 April 2004, Section II

(48) Date of publication of this corrected version:
1 April 2004

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.